

Bimetal Thermometer (Adjustable Angle Type)



Gauge® All-Angle thermometer allows for easy temperature measuring from any position.



► Standard Features

- Complete 180° Adjustability
- All Stainless Steel Construction
- Hermetically Sealed (ASME B40.3)
- Accurate to 1% of Full Scale
- Silicone Fillable for Vibration
- 360° Case Rotation

GA4 — **025** — **2** — **C22** — **SS**

Models	Stem Length	Connection	Temperature Ranges	Options
Standard Models	Without thread	Standard Threaded	Fahrenheit Ranges	
GA2 = Model H (2" dial, reset)	025 = 2.5"	1 = 1/4" PT	F21 -40 TO 110°F	PS = Pointed Stem
	040 = 4"	2 = 1/2" PT	F22 20 TO 130°F	SF = Silicone Fill (max temp 288°C)
GA2.5 = Model F (2.5" dial, reset)	060 = 6"	5 = 3/4" PT	F23 30 TO 240°F	SS = 316 SS Stem
	090 = 9"	U = 1/2" PT Union	F24 30 TO 300°F	S3 = 3/8" dia. Stem
GA3 = Model L (3" dial, reset)	120 = 12"		F25 30 TO 400°F	PC = Acrylic Window
GA4 = Model M (4" dial, reset)	Include thread		F26 30 TO 570°F	PY = Polycarbonate Window
	025 = 2.5"		F27 30 TO 750°F	TG = Tempered Glass Window
GA5 = Model J (5" dial, reset)	040 = 4"		F28 30 TO 950°F	MM = Max/Min Pointer
	060 = 6"		Celsius Ranges	CC = Certificate of Conformance
	090 = 9"		C21 -40 TO 40°C	C1 = 1 Point Calibration Cert.
	120 = 12"		C22 -5 TO 55°C	C3 = 3 Point Calibration Cert.
			C23 0 TO 115°C	
			C24 0 TO 150°C	
			C25 0 TO 300°C	
			C26 0 TO 400°C	
			C27 0 TO 500°C	
			Dual F/C Ranges	
			D21 -40 TO 110°F & -40 TO 40°C	
			D22 20 TO 130°F & -5 TO 55°C	
			D23 30 TO 240°F & 0 TO 115°C	
			D24 30 TO 300°F & 0 TO 150°C	
			D25 30 TO 400°F & 0 TO 150°C	
			D26 30 TO 570°F & 0 TO 300°C	
			D27 30 TO 750°F & 0 TO 400°C	
			D28 30 TO 950°F & 0 TO 500°C	

