

GENERAL PURPOSE GAUGES (DRY) G4PG



► Specifications

Case: Black Painted Steel

Ring: Snap-In Window, Push-On Bezel, or Bayonet

Lens: Snap-In Plastic or Glass

Dial: Aluminum, Black Figures on White Background

Wetted Parts: Copper Alloy

Accuracy: 3-2-3% (1.6% Available)








Range: 0~10kg/cm² , 0~11kg/cm²



- Black Steel Cases
- Copper Alloy Wetted Parts
- Cost Effective Design
- Standard 3-2-3% Accuracy

HOW TO ORDER

G4PG 40 — 1 — A — 4

Dial:	Tube & Socket:	Mounting:	Connection:
15 = 1.5"	1 = Copper Alloy 2 = SUS Alloy	A =  Bottom (All)	8 = 1/8" PT/NPT
20 = 2"		B =  Bottom/Rear Flange (2.5" , 3" , 4" , 6")	4 = 1/4" PT/NPT (2.5")
25 = 2.5"		C =  Back (1.5" , 2" , 2.5")  (4")	2 = 1/2" PT/NPT (4")
30 = 3"			Options:
40 = 4"		D =  Back /" U" or "O" Clamp (not avail. on "y" case)	
	E =  Back/Fr. Flange (2.5")  (4")	• High Temperatures (up to 380°F)	